

## SPL 3000c1



### Specifications:

Channels	no	<b>1</b>
Class	Typ	<b>D</b>
Power @14,4V /3.0% THD		
@ 4 ohm:	Wrms	<b>1000</b>
@ 2 ohm:	Wrms	<b>1850</b>
@ 1 ohm:	Wrms	<b>3100</b>
Operation supply	V	<b>10 -16</b>
Thermal protection	°C	<b>80</b>
THD @ 4 Ω / 50% Pmax	%	<b>0,1</b>
Signal/noise	dB	<b>71</b>
Efficiency (4 ohm)	%	<b>88</b>
Input sensitivity	Vrms	<b>0,2-6</b>
Low input impedance	Ω	<b>20 k</b>
Damping @ 80 Hz		<b>187</b>
Power consumption, idle	A	<b>3</b>
Power cons. 4 Ω	A	<b>78</b>
Power cons. 2 Ω	A	<b>156</b>
Weight	kg	<b>7,42</b>
Dimensions	l/w/h	<b>524/235/52 mm</b>

### Features:

- Lowpass filter with 24 dB dB slope.
- Subsonic filter
- Phase shift 0 - 180°
- Bass adjust 0 – 12 dB
- Optional remote available

### Miscellaneous:

- Protection for overhead, over current, short circuitry and speaker DC protection
- Massive heavy aluminum-heat sink